



Cement Products Portfolio

THE WORKRITE® DIFFERENCE

Our industry reputation is unparalleled for enhanced board life, workability, water retention, and durability. With a standard kit of 60 colors, our selection can meet most project needs. Custom colors can be manufactured by special order, and our staff is available for consultation on your project. Please call 717.792.4700, or email sales@workrite-cements.com.

WORKRITE® FORMULATIONS:

- TYPE O: A special tuckpoint masonry cement, typically used for restoration work.
- TYPE N: Used for construction above-grade and is recommended for exterior brick and block veneers.
- TYPE S: A stronger mix that can be used above/below grade.
- TYPE M: Our strongest mix. Used where additional compressive strengths are required. Available by special order only.

SAMPLES & CERTIFICATION:


Sample bags for pre-construction test panels are available through any authorized Workrite masonry supply dealer or your Workrite sales representative. For added convenience, Mill Test Reports, certification letters, and SDS sheets can be easily downloaded at workrite-cements.com.



5952 Lincoln Hwy West, Thomasville, PA 17364
workrite-cements.com

Pigmented Products

MASONRY CEMENTS



Type N

70 lbs./31.7 kg
40 bags/pallet

A general purpose cement that is formulated for veneer, load-bearing, and soft stone masonry construction. It is used to make masonry mortar when mixed with mason sand and water. *Meets ASTM C 91, C 270, C 979*



Type S

75 lbs./34 kg
40 bags/pallet

A higher-strength cement than Type-N, Type-S cement is formulated for veneer and load-bearing construction. It is used to make masonry mortar when mixed with mason sand and water. *Meets ASTM C 91, C 270, C 979*



Type O

75 lbs./34 kg
40 bags/pallet

A masonry cement typically used in blending restoration mortar. This specialty mortar is breathable and flexible, protecting brittle masonry units from moisture and freeze-thaw damage.

Meets ASTM C 91, C 270, C 979, C 780

MORTAR CEMENTS



Type N

60 lbs./27.2 kg
40 bags/pallet

Pre-Blended
With



Developed for use in structural applications where high flexural bond strength is required, e.g., high seismic areas. Type-N is a normal strength formulation.

Meets ASTM C 1329, C 270, C 979



Type S

65 lbs./29.5 kg
40 bags/pallet

Pre-Blended
With



Developed for use in structural applications where high flexural bond strength is required, e.g. high seismic areas. Type-S is a higher-strength formulation.

Meets ASTM C 1329, C 270, C 979

PC/L




Type N

72 lbs./32.7 kg
40 bags/pallet

A specific blend of Portland cement and hydrated lime, formulated for veneer and load-bearing construction.

Meets ASTM C 150, C 207, C 270, C 979



Type S

72 lbs./32.7 kg
40 bags/pallet

A specific blend of Portland cement and hydrated lime, formulated for veneer and load-bearing construction.

Meets ASTM C 150, C 207, C 270, C 979

PORTLAND



Type 1

94 lbs./42.6 kg
35 bags/pallet

This 100% Portland cement product is used to make our strongest mortar. It is perfect for laying real stone or using it on masonry projects where the highest strengths are required, and color is necessary. *Meets ASTM C 150*

Non-Pigmented Products

MORTAR CEMENTS



Type N

60 lbs./27.2 kg
40 bags/pallet

Pre-Blended
With



Developed for use in structural applications where high flexural bond strength is required, e.g. high seismic areas. Type-N is a normal strength formulation. Typically used for above-grade construction where color is not needed.

Meets ASTM C 1329, C 207, C 270



Type S

65 lbs./29.5 kg
40 bags/pallet

Pre-Blended
With



Developed for use in structural applications where high flexural bond strength is required, e.g. high seismic areas. Type-S is a higher-strength formulation. Typically used for above- and below-grade masonry construction where color is not needed. Meets ASTM C 1329, C 207, C 270

MASONRY CEMENT



Type O

75 lbs./34 kg
40 bags/pallet

A masonry cement typically used in blending restoration mortar. This mortar is breathable and flexible, protecting brittle masonry units from moisture and freeze-thaw damage. Typically used for above-grade construction where color is not needed. Meets ASTM C 91, C 270

PC/L



Type N

72 lbs./32.7 kg
40 bags/pallet

Featuring a specific blend of Portland cement and hydrated lime. Typically used for veneer and load-bearing masonry construction where color is not needed.

Meets ASTM C 150, C 207, C 270, C 979



Type S

72 lbs./32.7 kg
40 bags/pallet

Featuring a specific blend of Portland cement and hydrated lime. Typically used for above- and below-grade masonry construction where color is not needed.

Meets ASTM C 150, C 207, C 270, C 979

WORKRITE® cements are packaged in multi-layered bags for added security. Type-M formulations are available by special order.

FOR WHITE OR PALE
COLORED MORTARS:



White Mason
Sand

FOR ALL OTHER
MORTAR COLORS:



Straight Mason
Sand


SAND SELECTION IS IMPORTANT.

To achieve accurate color representation of your mortar, it's important to remember that the sand blended with our colored cements plays a key role in the final color outcome. We strongly recommend building a sample panel using actual job-site materials and obtaining approval before beginning construction. York Building Products' Aggregates Division offers a wide range of mason sands designed to complement your specific mortar selection.






Product Colors

Bring your vision to life with our standard palette of 60 colors spanning a wide range of hues. Looking for something unique? We offer custom color blending to match your exact project needs (minimum qtys apply). For added convenience, 16 of our most popular colors are in stock in Type N and Type S Masonry Cement—ready for fast delivery when you need it.

STOCK COLORS:

			
PORT WR-2029	RIVERSTONE WR-2380	OLIVE WR-2901	SAWGRASS WR-2081
			
GRAPHITE WR-2070	ALMOND WR-2900	BUCKSKIN WR-2223	DRIFTWOOD WR-2224
			
MUSHROOM WR-446	ARCTIC WHITE WR-103(W.S)	OLDE COLONY WR-2906	MORNING MIST WR-2247A
			
BIRCH WR-2320	GLACIER WR-280	MALT WR-2073	CLAY WR-2904

STANDARD COLORS:

			
CHESTNUT WR-2368	SUNSET WR-2206	SAWDUST WR-2342	THISTLE WR-2105
			
RAW UMBER WR-2246	MAUVE WR-2220	SHELL WR-2216	ACORN WR-2113
			
ESPRESSO WR-2024	BLUSH WR-2905	BISQUE WR-2039	PEBBLE WR-2106
			
APPALACHIAN WR-2088	SALZBURG WR-2774	CURRY WR-2249	SUEDE WR-2158
			
TIMBER WR-2002	TERRACOTTA WR-2273	PATAGONIA WR-2311	CANYON WR-2031
			
COCOA WR-2259	AMBER WR-2207	SAGE WR-2902	SAND WR-2443
			
REDWOOD WR-2492	FALLOW WR-2251	WHEAT WR-2907	CHAMPAGNE WR-2084
			
MAHOGANY WR-2181	TAUPE WR-2412	RIDGE WR-2287	SLATE WR-2410
			
MEDITERRANEAN WR-2324	CINDER WR-2295	MERINO WR-2119	GRAVEL WR-2055
			
AUTUMN WR-2208	MARBLE WR-2185	GRAIN WR-2243	PEWTER WR-2057
			
BURNT SIENNA WR-2272	PRAIRIE WR-2247	CANVAS WR-2244	SMOKE WR-2062

